

CB シリーズ (1 リール 1000 本入)

RoHS対応

- 適合はさみ込み用治具は、品番 CBX-100 です。

Technical drawing of a mechanical part showing front and top views with dimensions.


Front View Dimensions:

- Top flange width: 1.0
- Top flange thickness: 0.25
- Overall height: 10.4
- Distance from base to top flange: 4.0
- Distance from base to start of top flange: 0.5
- Base diameter: $\phi 2$
- Base hole diameter: 2.54
- Base hole spacing: 5.08

Top View Dimensions:

- Overall width: B
- Inner width: A
- Distance from center to hole center: $r_{1.2}$
- Hole diameter: 0.6
- Distance from center to hole center: C
- Overall width: 0.25

CB-1-1, 1-2, 1-3



Technical drawing of a mechanical part showing front and side views with dimensions.

Front View Dimensions:


- Top flange width: 1.2
- Top flange thickness: 0.5
- Stem diameter: $\phi 2$
- Stem length: 8.0 (15.3)
- Base diameter: 5.08
- Base thickness: 2.54
- Base hole diameter: $\phi 2$

Side View Dimensions:

- Top flange width: B
- Top flange thickness: A
- Stem diameter: $\phi 2$
- Stem length: 0.7
- Base diameter: 0.25
- Base thickness: 2.6
- Base hole diameter: C

CB-1-4, 1-5

CB-2-1, 2-2, 2-3, 2-4



- 代替品 CB-□-□- A になります。
従来品の末尾に " - A " を付与した品番。

(変更点) めっき処理が「ニッケル下地スズめっき (光沢)」へ変更
※形状・寸法、材質などその他は変更ありません。

Technical drawing of a mechanical part, showing front and side views with dimensions.

Front View (Left):

- Overall width: 1.6
- Overall height: 16.5
- Top section width: 1.25
- Top section height: 3.0
- Section below top: 1.75
- Section below that: 0.45
- Bottom section height: 7.25
- Bottom section width: 2.54
- Bottom section height: 2.54
- Bottom section width: 2.54

Side View (Right):

- Overall width: 0.25
- Top section width: C
- Top section height: A
- Section below top: 2.2
- Section below that: B

CB-2-5